

Atlantic Ultraviolet Sanitaire RS72

free standing, wall or ceiling mount in occupied areas



- **STER-L-RAY® Germicidal Ultraviolet Lamp(s)** Lamp(s) are instant starting and provide the utmost in quality, sustained output, and longevity (see page 11 for more information).
- **Interlock Safety Switch** The interlock safety switch is a standard feature that disconnects power to the model when the access panel is unhinged for lamp or filter replacement (located under the cover).
- **Steadfast™ Lampholders Set** includes a stationary and a springloaded, telescopic holder that holds a single pin lamp securely. The springloaded feature on one end facilitates convenient, quick and easy lamp changes.
- **Surelite™ Ballast(s)** State-of-the-art electronic ballast specifically developed for the operation of ultraviolet lamps. Versatile ballast provides high lamp
- **Promate™ Observation Port/ Sight Glass Assembly** A Sight Glass Assembly allows for visual inspection of the lamp(s). output; is lightweight, efficient, and operates cool for longer life.
- **Promate™ Particulate Filter(s) • Washable Electrostatic Filter** (on all models) • **Absolute Filter - HEPA Type** (on Model RSA760)

Model	RS72
Nominal Model Capacity (m ³ /min)	1.53
Dimensions (mm)	876x197x197
Electrical Requirements* (amps)	1.25
Max. Room Size Treated at 3 Room Air Changes/Hour (m ³)	31
Max. Room Size Treated at 6 Room Air Changes/Hour (m ³)	15
Max. Treatment Capacity (m ³ /h)	92
Lamp No.	05-1348-R
Lamp Length	556mm
Lamp Length (including lampholders)	610mm
Power Consumption	30.7 W
Ultraviolet Output (per lamp)	8.5 W
Rated Average Effective Life	10,000 Hours



SPECTRA®
PROFESSIONAL UV SOLUTIONS

str. Zizinului nr. 110, Braşov, 500407, România

www.akro.ro | www.spectra.ro

+40 770 717 189

office@akro.ro